



## Features

### Android OS.

The NQure 750 Stingray uses Android 7.1 OS. With this reliable operating system comes a feature-rich environment for stable apps that are tried and tested. Android 7.1 is an excellent match for the applications most suited to the NQure 750. Particularly when operating within four walls, fitting the NQure 750's PoE (Power over Ethernet) connectivity.

### Free MDM included.

The NQure 750 Stingray comes with the option of running Newland's free MDM solution: Ndevor. As a result, the Micro Kiosk lends itself perfectly for the coordination of multiple units. Managing information from a shared database, organizing applications and settings across many individual units, as well as low-touch assistance in troubleshooting can all be managed from a centralized location.

### Mount anywhere.

The NQure 750 Stingray's slimline and lightweight design is suitable for mounting on any shelf edge. Options to mount the Nquire series range from shelf to wall and free-standing. Its classic Vesa75 configuration also ensures existing industry standard, 3rd party solutions are compatible.

### Snappy Megapixel Scanning.

Barcode data capture is at the heart of Newland's Micro Kiosks and so the NQure 750 is fitted with their own Megapixel scanning technology. This maintains high standards for the scanning of both large and small 1D & 2D barcodes. The Micro Kiosk further includes optimal settings for reading barcodes presented on smartphone and tablet screens. With the scanner set at a 20° angle, it matches the ergonomics of how the user presents codes for scanning.

### Multi-purpose display.

The sharp, full-colour screen on the Stingray is perfect for running animations and live recorded videos when not actively being used. With onboard memory, expanded memory and online options, the choice of content to display is virtually limitless.

### Endless communication possibilities.

With WiFi, Ethernet, Powered Ethernet (PoE) and Bluetooth, this Micro Kiosk offers a variety of standard communication possibilities. Additionally, optional 4G means that the NQure 750 Stingray can communicate and be communicated with, no matter the circumstance. Adding to that the wide variety of data capture options, such as integrated barcode reading, MSR, NFC and low frequency RFID, application possibilities are endless.



## Application Scenarios



access control



hospitality



inventory



point of sale



retail



self service



ticketing



transportation

# NQuire 750 Stingray technical specifications

<b>Performance</b>	Operating System	Android 7.1
	Processor	1.5GHz octa-core 64-bit
	Memory RAM	2GB DDR3
	Memory Flash	8GB Emmc
	Memory Storage Expansion (Max.)	Micro SD card up to 128GB
	Image Sensor	1280 x 800 CMOS
	Illumination	White LED
	Aiming	650nm laser diode
	Depth of Field EAN13 (13mil)	70-600mm
	Depth of Field CODE 39 (5mil)	120-280mm
	Depth of Field PDF417 (6.67mil)	110-230mm
	Depth of Field Data Matrix (10mil)	110-260mm
	Depth of Field QR (15mil)	55-400mm
	Minimal Print Contrast	25%
	Scan Angle Roll	360°
	Scan Angle Pitch	±50°
	Scan Angle Skew	±50°
Field of View Horizontal	42°	
Field of View Vertical	28°	
<b>Data capture</b>	1D	Code128, EAN-13, EAN-8, Code39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, ITF-6, ITF-14, ISBN, Code 93, UCC/EAN-128, GS1 Databar, GS1 Composite Code, Matrix 2 of 5, Code11, Industrial 25, Standard 25, Plessey, MSI-Plessey, etc.
	2D	PDF417, QR Code, Data Matrix, Chinese Sensible Code, Aztec Code, Maxicode, MicroPDF417*, etc.
<b>Physical</b>	Dimensions (mm)	195(H)x138.5(W)x25(D)mm
	VESA	Complies with the standard VESA 75 bracket, enabling easy mounting on shelves and walls
	Display	7" 1280x800 IPS display
	Touch panel	5-point capacitive touch panel
	Interfaces	USB 2.0 host, type A port, micro USB 2.0 type B, OTG, programmable GPIO (2 in - 2 out)
	Input Voltage	DC12V, 2A
	Power Consumption	12W (MAX)
	Power Supply Input	AC110 ~ 220V, 50~60Hz
	Power Supply Output	DC12V, 2A
	Sensors	Gravity Sensor
	Power over Ethernet	IEEE 802.3af
	Audio	82dB dual-channel stereo sound speaker
Expansion Slot	Micro SD up to 128GB	
<b>Environmental</b>	Operating Temperature	0°C to 40°C (32°F to 104°F)
	Storage Temperature	-10°C to 55°C (14°F to 131°F)
	Humidity	20% to 65% (40°C)
	Sealing	IP54
<b>Wireless</b>	WLAN Radio	IEEE 802.11 a/b/g/n/ac, 2.4GHz and 5GHz (optional)
	WPAN Radio	Bluetooth 4.0 LE, EDR + BLE (optional)
	RFID	ISO/IEC 14443 A/B ISO/IEC 15693; MIFARE 1K/4K; MIFARE DESFire; Sony FelIca (optional)
<b>Device Management</b>	Software	Ndevor (MDM, Device Configuration), SOTi (MDM), StayLinked (TE)
<b>Certifications</b>	Certifications	CE, RoHS, IEC/EN 62471
<b>Warranty</b>	Warranty	2 years